

856 Ship Notice/Manifest

X12/V5010/856 : 856 Ship Notice/Manifest

Author:	SPS Commerce
Company:	Academy Sports and Outdoors

Table of Contents

856	Ship Notice/Manifest	1
	ST Transaction Set Header	3
	BSN Beginning Segment for Ship Notice	4
	HL Loop Hierarchical Level	5
	HL Hierarchical Level	6
	TD1 Carrier Details (Quantity and Weight)	7
	REF Reference Information	8
	DTM Date/Time Reference	9
	N1 Loop Party Identification	10
	N1 Party Identification	11
	HL Loop Hierarchical Level	12
	HL Hierarchical Level	13
	PRF Purchase Order Reference	14
	REF Reference Information	15
	N1 Loop Party Identification	16
	N1 Party Identification	17
	HL Loop Hierarchical Level	18
	HL Hierarchical Level	19
	MAN Marks and Numbers Information	20
	HL Loop Hierarchical Level	21
	HL Hierarchical Level	22
	LIN Item Identification	23
	SN1 Item Detail (Shipment)	25
	REF Reference Information	26
	SE Transaction Set Trailer	27

856 Ship Notice/Manifest

Functional Group=SH

Purpose: This X12 Transaction Set contains the format and establishes the data contents of the Ship Notice/Manifest Transaction Set (856) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to list the contents of a shipment of goods as well as additional information relating to the shipment, such as order information, product description, physical characteristics, type of packaging, marking, carrier information, and configuration of goods within the transportation equipment. The transaction set enables the sender to describe the contents and configuration of a shipment in various levels of detail and provides an ordered flexibility to convey information. The sender of this transaction is the organization responsible for detailing and communicating the contents of a shipment, or shipments, to one or more receivers of the transaction set. The receiver of this transaction set can be any organization having an interest in the contents of a shipment or information about the contents of a shipment.

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
0100	ST	Transaction Set Header	M	1			Must use
0200	BSN	Beginning Segment for Ship Notice	M	1			Must use

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
<u>LOOP ID - HL</u>					<u>200000</u>	<u>C2/0100L</u>	
0100	HL	Hierarchical Level	M	1		C2/0100	Must use
1100	TD1	Carrier Details (Quantity and Weight)	M	1			Must use
1500	REF	Reference Information	O	2			Used
2000	DTM	Date/Time Reference	M	1			Must use
<u>LOOP ID - N1</u>					<u>1</u>		
2200	N1	Party Identification	M	1			Must use
<u>LOOP ID - HL</u>					<u>200000</u>	<u>C2/0100L</u>	
0100	HL	Hierarchical Level	M	1		C2/0100	Must use
0500	PRF	Purchase Order Reference	M	1			Must use
1500	REF	Reference Information	M	1			Must use
<u>LOOP ID - N1</u>					<u>1</u>		
2200	N1	Party Identification	O	1			Used
<u>LOOP ID - HL</u>					<u>200000</u>	<u>C2/0100L</u>	
0100	HL	Hierarchical Level	M	1		C2/0100	Must use
1900	MAN	Marks and Numbers Information	M	1			Must use
<u>LOOP ID - HL</u>					<u>200000</u>	<u>C2/0100L</u>	
0100	HL	Hierarchical Level	M	1		C2/0100	Must use
0200	LIN	Item Identification	M	1			Must use
0300	SN1	Item Detail (Shipment)	M	1			Must use
1500	REF	Reference Information	O	>1			Used

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
0200	SE	Transaction Set Trailer	M	1			Must use

Comments:

- 2/0100L The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/0100 The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/0100L The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/0100 The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/0100L The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/0100 The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/0100L The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/0100 The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.

User Note 1:*Change History*

1/31/2019

- Moved N1 segment for Mark For (N101 = Z7) from the Pack level to the Order level

7/24/2023

- Added Serial Number (REF01=SE) to the item level.

ST Transaction Set Header

Pos: 0100	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use

Description: Code uniquely identifying a Transaction Set

CodeList Summary (Total Codes: 318, Included: 1)

Code Name

856 Ship Notice/Manifest

ST02	329	Transaction Set Control Number	M	AN	4/9	Must use
------	-----	--------------------------------	---	----	-----	----------

Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set

Semantics:

1. The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
2. The implementation convention reference (ST03) is used by the translation routines of the interchange partners to select the appropriate implementation partners convention to match the transaction set definition. When used, this implementation convention reference takes precedence over the implementation reference specified in the GS08.

BSN Beginning Segment for Ship Notice

Pos: 0200	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 5

User Option (Usage): Must use

Purpose: To transmit identifying numbers, dates, and other basic data relating to the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BSN01	353	Transaction Set Purpose Code	M	ID	2/2	Must use
Description: Code identifying purpose of transaction set						
CodeList Summary (Total Codes: 66, Included: 1)						
Code Name						
00 Original						
BSN02	396	Shipment Identification	M	AN	2/30	Must use
Description: A unique control number assigned by the original shipper to identify a specific shipment						
BSN03	373	Date	M	DT	8/8	Must use
Description: Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year						
BSN04	337	Time	M	TM	4/8	Must use
Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)						
BSN05	1005	Hierarchical Structure Code	O	ID	4/4	Used
Description: Code indicating the hierarchical application structure of a transaction set that utilizes the HL segment to define the structure of the transaction set						
CodeList Summary (Total Codes: 81, Included: 1)						
Code Name						
0001 Shipment, Order, Packaging, Item						

Syntax Rules:

1. C0706 - If BSN07 is present, then BSN06 is required.

Semantics:

1. BSN03 is the date the shipment transaction set is created.
2. BSN04 is the time the shipment transaction set is created.
3. BSN06 is limited to shipment related codes.

Comments:

1. BSN06 and BSN07 differentiate the functionality of use for the transaction set.

Loop Hierarchical Level

Pos: 0100 Repeat: 200000
 Mandatory
 Loop: HL Elements: N/A

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0100	HL	Hierarchical Level	M	1		Must use
1100	TD1	Carrier Details (Quantity and Weight)	M	1		Must use
1500	REF	Reference Information	O	2		Used
2000	DTM	Date/Time Reference	M	1		Must use
2200		Loop N1	M		1	Must use
0100		Loop HL	M		200000	Must use

HL Hierarchical Level

Pos: 0100	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 2

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use

Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure

HL03	735	Hierarchical Level Code	M	ID	1/2	Must use
------	-----	--------------------------------	---	----	-----	----------

Description: Code defining the characteristic of a level in a hierarchical structure

CodeList Summary (Total Codes: 250, Included: 1)

Code Name

S Shipment

Comments:

1. The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
2. The HL segment defines a top-down/left-right ordered structure.
3. HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
4. HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
5. HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
6. HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

TD1 Carrier Details (Quantity and Weight)

Pos: 1100	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 2

User Option (Usage): Must use

Purpose: To specify the transportation details relative to commodity, weight, and quantity

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TD101	103	Packaging Code	M	AN	3/5	Must use

Description: Code identifying the type of packaging; Part 1: Packaging Form, Part 2: Packaging Material; if the Data Element is used, then Part 1 is always required

CodeList Summary (Total Codes: 155, Included: 1)

<u>Code</u>	<u>Name</u>
CTN	Carton

TD102	80	Lading Quantity	M	N0	1/7	Must use
-------	----	-----------------	---	----	-----	----------

Description: Number of units (pieces) of the lading commodity

Syntax Rules:

1. C0102 - If TD101 is present, then TD102 is required.
2. C0304 - If TD103 is present, then TD104 is required.
3. C0607 - If TD106 is present, then TD107 is required.
4. P0708 - If either TD107 or TD108 is present, then the other is required.
5. P0910 - If either TD109 or TD110 is present, then the other is required.

REF Reference Information

Pos: 1500	Max: 2
Detail - Optional	
Loop: HL	Elements: 2

User Option (Usage): Used

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

CodeList Summary (Total Codes: 1731, Included: 2)

Code Name

BM Bill of Lading Number

SN Seal Number

REF02	127	Reference Identification	M	AN	1/50	Must use
-------	-----	--------------------------	---	----	------	----------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

User Note 1: *Max length when REF01 = BM is 17 characters*

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

DTM Date/Time Reference

Pos: 2000	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 2

User Option (Usage): Must use

Purpose: To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use

Description: Code specifying type of date or time, or both date and time

CodeList Summary (Total Codes: 1280, Included: 1)

Code Name

011 Shipped

DTM02	373	Date	M	DT	8/8	Must use
-------	-----	------	---	----	-----	----------

Description: Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year

Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

Loop Party Identification

Pos: 2200	Repeat: 1
Mandatory	
Loop: N1	Elements: N/A

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
2200	N1	Party Identification	M	1		Must use

N1 Party Identification

Pos: 2200	Max: 1
Detail - Mandatory	
Loop: N1	Elements: 3

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use
Description: Code identifying an organizational entity, a physical location, property or an individual						
CodeList Summary (Total Codes: 1500, Included: 1)						
Code Name						
ST Ship To						
N103	66	Identification Code Qualifier	M	ID	1/2	Must use
Description: Code designating the system/method of code structure used for Identification Code (67)						
CodeList Summary (Total Codes: 241, Included: 1)						
Code Name						
92 Assigned by Buyer or Buyer's Agent						
N104	67	Identification Code	M	AN	2/80	Must use
Description: Code identifying a party or other code						

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

Loop Hierarchical Level

Pos: 0100 Repeat: 200000
 Mandatory
 Loop: HL Elements: N/A

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0100	HL	Hierarchical Level	M	1		Must use
0500	PRF	Purchase Order Reference	M	1		Must use
1500	REF	Reference Information	M	1		Must use
2200		Loop N1	O		1	Used
0100		Loop HL	M		200000	Must use

HL Hierarchical Level

Pos: 0100	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 3

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use
Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure						
HL02	734	Hierarchical Parent ID Number	M	AN	1/12	Must use
Description: Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to						
HL03	735	Hierarchical Level Code	M	ID	1/2	Must use
Description: Code defining the characteristic of a level in a hierarchical structure						
CodeList Summary (Total Codes: 250, Included: 1)						
<u>Code</u> <u>Name</u>						
O Order						

Comments:

1. The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
2. The HL segment defines a top-down/left-right ordered structure.
3. HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
4. HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
5. HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
6. HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

PRF Purchase Order Reference

Pos: 0500	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 1

User Option (Usage): Must use

Purpose: To provide reference to a specific purchase order

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PRF01	324	Purchase Order Number	M	AN	1/22	Must use

Description: Identifying number for Purchase Order assigned by the orderer/purchaser

Semantics:

1. PRF04 is the date assigned by the purchaser to purchase order.

REF Reference Information

Pos: 1500	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 2

User Option (Usage): Must use

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

CodeList Summary (Total Codes: 1731, Included: 1)

Code Name

IA Internal Vendor Number

REF02	127	Reference Identification	M	AN	1/50	Must use
-------	-----	--------------------------	---	----	------	----------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

Loop Party Identification

Pos: 2200	Repeat: 1
Optional	
Loop: N1	Elements: N/A

User Option (Usage): Used

Purpose: To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
2200	N1	Party Identification	O	1		Used

N1 Party Identification

Pos: 2200	Max: 1
Detail - Optional	
Loop: N1	Elements: 3

User Option (Usage): Used

Purpose: To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use
<p>Description: Code identifying an organizational entity, a physical location, property or an individual</p> <p>CodeList Summary (Total Codes: 1500, Included: 1)</p> <p>Code Name</p> <p>Z7 Mark-for Party</p>						
N103	66	Identification Code Qualifier	M	ID	1/2	Must use
<p>Description: Code designating the system/method of code structure used for Identification Code (67)</p> <p>CodeList Summary (Total Codes: 241, Included: 1)</p> <p>Code Name</p> <p>92 Assigned by Buyer or Buyer's Agent</p>						
N104	67	Identification Code	M	AN	2/80	Must use
<p>Description: Code identifying a party or other code</p>						

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

Loop Hierarchical Level

Pos: 0100	Repeat: 200000
Mandatory	
Loop: HL	Elements: N/A

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0100	HL	Hierarchical Level	M	1		Must use
1900	MAN	Marks and Numbers Information	M	1		Must use
0100		Loop HL	M		200000	Must use

HL Hierarchical Level

Pos: 0100	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 3

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use
Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure						
HL02	734	Hierarchical Parent ID Number	M	AN	1/12	Must use
Description: Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to						
HL03	735	Hierarchical Level Code	M	ID	1/2	Must use
Description: Code defining the characteristic of a level in a hierarchical structure						
CodeList Summary (Total Codes: 250, Included: 1)						
<u>Code</u> <u>Name</u>						
P Pack						

Comments:

1. The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
2. The HL segment defines a top-down/left-right ordered structure.
3. HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
4. HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
5. HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
6. HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

MAN Marks and Numbers Information

Pos: 1900	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 2

User Option (Usage): Must use

Purpose: To indicate identifying marks and numbers for shipping containers

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MAN01	88	Marks and Numbers Qualifier	M	ID	1/2	Must use

Description: Code specifying the application or source of Marks and Numbers (87)

CodeList Summary (Total Codes: 21, Included: 1)

Code Name

GM EAN.UCC Serial Shipping Container Code (SSCC) and Application Identifier

MAN02	87	Marks and Numbers	M	AN	1/48	Must use
-------	----	-------------------	---	----	------	----------

Description: Marks and numbers used to identify a shipment or parts of a shipment

User Note 1: *Must be a 20 character numeric number.*

Syntax Rules:

1. P0405 - If either MAN04 or MAN05 is present, then the other is required.
2. C0605 - If MAN06 is present, then MAN05 is required.

Semantics:

1. MAN01/MAN02 and MAN04/MAN05 may be used to identify two different marks and numbers assigned to the same physical container.
2. When both MAN02 and MAN03 are used, MAN02 is the starting number of a sequential range and MAN03 is the ending number of that range.
3. When both MAN05 and MAN06 are used, MAN05 is the starting number of a sequential range, and MAN06 is the ending number of that range.

Comments:

1. When MAN01 contains code "UC" (U.P.C. Shipping Container Code) and MAN05/MAN06 contain a range of ID numbers, MAN03 is not used. The reason for this is that the U.P.C. Shipping Container code is the same on every carton that is represented in the range in MAN05/MAN06.
2. MAN03 and/or MAN06 are only used when sending a range(s) of ID numbers.
3. When both MAN02/MAN03 and MAN05/MAN06 are used to send ranges of ID numbers, the integrity of the two ID numbers must be maintained.

Loop Hierarchical Level

Pos: 0100	Repeat: 200000
Mandatory	
Loop: HL	Elements: N/A

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0100	HL	Hierarchical Level	M	1		Must use
0200	LIN	Item Identification	M	1		Must use
0300	SN1	Item Detail (Shipment)	M	1		Must use
1500	REF	Reference Information	O	>1		Used

HL Hierarchical Level

Pos: 0100	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 3

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use
Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure						
HL02	734	Hierarchical Parent ID Number	M	AN	1/12	Must use
Description: Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to						
HL03	735	Hierarchical Level Code	M	ID	1/2	Must use
Description: Code defining the characteristic of a level in a hierarchical structure						
CodeList Summary (Total Codes: 250, Included: 1)						
<u>Code</u> <u>Name</u>						
I Item						

Comments:

1. The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
2. The HL segment defines a top-down/left-right ordered structure.
3. HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
4. HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
5. HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
6. HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

LIN Item Identification

Pos: 0200	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 6

User Option (Usage): Must use

Purpose: To specify basic item identification data

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
LIN02	235	Product/Service ID Qualifier	M	ID	2/2	Must use

Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)

CodeList Summary (Total Codes: 519, Included: 1)

Code Name

UP UCC - 12

LIN03	234	Product/Service ID	M	AN	1/48	Must use
-------	-----	--------------------	---	----	------	----------

Description: Identifying number for a product or service

User Note 1: 14 digit value is expected from the order

LIN04	235	Product/Service ID Qualifier	X	ID	2/2	Used
-------	-----	------------------------------	---	----	-----	------

Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)

CodeList Summary (Total Codes: 519, Included: 2)

Code Name

SK Stock Keeping Unit (SKU)

VN Vendor's (Seller's) Item Number

LIN05	234	Product/Service ID	X	AN	1/48	Used
-------	-----	--------------------	---	----	------	------

Description: Identifying number for a product or service

LIN06	235	Product/Service ID Qualifier	X	ID	2/2	Used
-------	-----	------------------------------	---	----	-----	------

Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)

CodeList Summary (Total Codes: 519, Included: 2)

Code Name

SK Stock Keeping Unit (SKU)

VN Vendor's (Seller's) Item Number

LIN07	234	Product/Service ID	X	AN	1/48	Used
-------	-----	--------------------	---	----	------	------

Description: Identifying number for a product or service

Syntax Rules:

1. P0405 - If either LIN04 or LIN05 is present, then the other is required.
2. P0607 - If either LIN06 or LIN07 is present, then the other is required.
3. P0809 - If either LIN08 or LIN09 is present, then the other is required.
4. P1011 - If either LIN10 or LIN11 is present, then the other is required.

5. P1213 - If either LIN12 or LIN13 is present, then the other is required.
6. P1415 - If either LIN14 or LIN15 is present, then the other is required.
7. P1617 - If either LIN16 or LIN17 is present, then the other is required.
8. P1819 - If either LIN18 or LIN19 is present, then the other is required.
9. P2021 - If either LIN20 or LIN21 is present, then the other is required.
10. P2223 - If either LIN22 or LIN23 is present, then the other is required.
11. P2425 - If either LIN24 or LIN25 is present, then the other is required.
12. P2627 - If either LIN26 or LIN27 is present, then the other is required.
13. P2829 - If either LIN28 or LIN29 is present, then the other is required.
14. P3031 - If either LIN30 or LIN31 is present, then the other is required.

Semantics:

1. LIN01 is the line item identification

Comments:

1. See the Data Dictionary for a complete list of IDs.
2. LIN02 through LIN31 provide for fifteen different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

User Note 1:

*All item identifiers must match what was sent on the 850 Purchase Order
Vendor SKU and Academy SKU must be less than 25 characters.*

SN1 Item Detail (Shipment)

Pos: 0300	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 2

User Option (Usage): Must use

Purpose: To specify line-item detail relative to shipment

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SN102	382	Number of Units Shipped	M	R	1/10	Must use

Description: Numeric value of units shipped in manufacturer's shipping units for a line item or transaction set

SN103	355	Unit or Basis for Measurement Code	M	ID	2/2	Must use
-------	-----	------------------------------------	---	----	-----	----------

Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken

CodeList Summary (Total Codes: 844, Included: 1)

Code Name

EA Each

Syntax Rules:

1. P0506 - If either SN105 or SN106 is present, then the other is required.

Semantics:

1. SN101 is the ship notice line-item identification.
2. SN105 is quantity ordered.

Comments:

1. SN103 defines the unit of measurement for both SN102 and SN104.

REF Reference Information

Pos: 1500	Max: >1
Detail - Optional	
Loop: HL	Elements: 2

User Option (Usage): Used

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	O	ID	2/3	Used

Description: Code qualifying the Reference Identification

CodeList Summary (Total Codes: 1731, Included: 1)

Code Name

SE Serial Number

REF02	127	Reference Identification	O	AN	1/50	Used
-------	-----	--------------------------	---	----	------	------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

SE Transaction Set Trailer

Pos: 0200	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments	M	N0	1/10	Must use
		Description: Total number of segments included in a transaction set including ST and SE segments				
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
		Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set				

Comments:

1. SE is the last segment of each transaction set.