

Frontgate and Grandin Road 846 Inventory Inquiry/Advice

X12/V5010/846 : 846 Inventory Inquiry/Advice

Author:	SPS Commerce
Company:	Frontgate and Grandin Road
Notes:	

Table of Contents

846	Inventory Inquiry/Advice	1
ST	Transaction Set Header	2
BIA	Beginning Segment for Inventory Inquiry/Advice	3
REF	Reference Information	4
N1	Loop Party Identification	5
N1	Party Identification	6
N3	Party Location	7
N4	Geographic Location	8
LIN	Loop Item Identification	9
LIN	Item Identification	10
PID	Product/Item Description	12
QTY	Loop Quantity Information	13
QTY	Quantity Information	14
DTM	Date/Time Reference	15
CTT	Transaction Totals	16
SE	Transaction Set Trailer	17

846 Inventory Inquiry/Advice

Functional Group=IB

Purpose: This X12 Transaction Set contains the format and establishes the data contents of the Inventory Inquiry/Advice Transaction Set (846) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used in the following ways: (1) for a seller of goods and services to provide inventory information to a prospective purchaser, with no obligation to the purchaser to acquire these goods or services; (2) for a representative of a seller of goods and services to supply inventory information to that seller; (3) for one location to supply another location with inventory information; and (4) for an inquiry as to the availability of inventory with no obligation on the seller of goods and services to reserve that inventory.

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Reg</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
0100	ST	Transaction Set Header	M	1			Must use
0200	BIA	Beginning Segment for Inventory Inquiry/Advice	M	1			Must use
0600	REF	Reference Information	M	1			Must use
LOOP ID - N1					<u>1</u>		
0800	N1	Party Identification	M	1			Must use
1000	N3	Party Location	O	1			Used
1100	N4	Geographic Location	O	1			Used

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Reg</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP ID - LIN					<u>10000</u>		
0100	LIN	Item Identification	M	1			Must use
0300	PID	Product/Item Description	M	10			Must use
LOOP ID - QTY					<u>99</u>		
3200	QTY	Quantity Information	M	1			Must use
3550	DTM	Date/Time Reference	M	1			Must use

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Reg</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
0100	CTT	Transaction Totals	O	1		N3/0100	Used
0200	SE	Transaction Set Trailer	M	1			Must use

Notes:

3/0100 Number of line items (CTT01) is the accumulation of number of LIN segments. If used, hash total (CTT02) is the sum of the values of the quantities (QTY02) of each QTY segment.

User Note 1:

Available Inventory (846) Vendor Usage Notes:

Vendors will be expected to send 846 files at least once a day representing available inventory .

Frontgate and Grandin Road would prefer to receive files that only include Frontgate and Grandin Road items; however, will accept vendors files that include a vendor's full item catalog.

The quantities included will represent corporate level quantities regardless of the number of Ship-From locations a vendor has.

Include those items that may have zero inventories.

ST Transaction Set Header

Pos: 0100	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use

Description: Code uniquely identifying a Transaction Set

CodeList Summary (Total Codes: 318, Included: 1)

Code Name

846 Inventory Inquiry/Advice

ST02	329	Transaction Set Control Number	M	AN	4/9	Must use
------	-----	--------------------------------	---	----	-----	----------

Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set

Semantics:

1. The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
2. The implementation convention reference (ST03) is used by the translation routines of the interchange partners to select the appropriate implementation convention to match the transaction set definition. When used, this implementation convention reference takes precedence over the implementation reference specified in the GS08.

BIA Beginning Segment for Inventory Inquiry/Advice

Pos: 0200	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 5

User Option (Usage): Must use

Purpose: To indicate the beginning of an Inventory Inquiry/Advice Transaction Set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BIA01	353	Transaction Set Purpose Code	M	ID	2/2	Must use
Description: Code identifying purpose of transaction set CodeList Summary (Total Codes: 66, Included: 1) <u>Code</u> <u>Name</u> 00 Original						
BIA02	755	Report Type Code	M	ID	2/2	Must use
Description: Code indicating the title or contents of a document, report or supporting item CodeList Summary (Total Codes: 541, Included: 1) <u>Code</u> <u>Name</u> MB Manufacturer/Distributor Inventory Report						
BIA03	127	Reference Identification	M	AN	1/50	Must use
Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier						
BIA04	373	Date	M	DT	8/8	Must use
Description: Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year User Note 1: <i>Inventory Advice Date</i>						
BIA05	337	Time	O	TM	4/8	Used
Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99) User Note 1: <i>Inventory Advice Time</i>						

Semantics:

1. BIA03 identifies the number of the inquiry/advice that is transferred.
2. BIA04 identifies the date of the inquiry/advice that is transferred.
3. BIA05 identifies the time of the inquiry/advice that is transferred.

REF Reference Information

Pos: 0600	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

CodeList Summary (Total Codes: 1731, Included: 1)

Code Name

IA Internal Vendor Number

User Note 1:

Mandatory - Frontgate and Grandin Road assigned Vendor ID

REF02	127	Reference Identification	M	AN	1/50	Must use
-------	-----	--------------------------	---	----	------	----------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

Loop Party Identification

Pos: 0800	Repeat: 1
Mandatory	
Loop: N1	Elements: N/A

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0800	N1	Party Identification	M	1		Must use
1000	N3	Party Location	O	1		Used
1100	N4	Geographic Location	O	1		Used

N1 Party Identification

Pos: 0800	Max: 1
Heading - Mandatory	
Loop: N1	Elements: 4

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use
Description: Code identifying an organizational entity, a physical location, property or an individual CodeList Summary (Total Codes: 1500, Included: 1) <u>Code</u> <u>Name</u> RL Reporting Location						
N102	93	Name	M	AN	1/60	Must use
Description: Free-form name						
N103	66	Identification Code Qualifier	X	ID	1/2	Used
Description: Code designating the system/method of code structure used for Identification Code (67) CodeList Summary (Total Codes: 241, Included: 1) <u>Code</u> <u>Name</u> 91 Assigned by Seller or Seller's Agent						
N104	67	Identification Code	X	AN	2/80	Used
Description: Code identifying a party or other code						

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

N3

Party Location

Pos: 1000

Max: 1

Heading - Optional

Loop: N1

Elements: 2

User Option (Usage): Used
Purpose: To specify the location of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	Address Information	M	AN	1/55	Must use
		Description: Address information				
N302	166	Address Information	O	AN	1/55	Used
		Description: Address information				

N4 Geographic Location

Pos: 1100	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used

Purpose: To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name	O	AN	2/30	Used
		Description: Free-form text for city name				
N402	156	State or Province Code	O	ID	2/2	Used
		Description: Code (Standard State/Province) as defined by appropriate government agency				
N403	116	Postal Code	O	ID	3/15	Used
		Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)				
N404	26	Country Code	X	ID	2/3	Used
		Description: Code identifying the country				

Syntax Rules:

1. E0207 - Only one of N402 or N407 may be present.
2. C0605 - If N406 is present, then N405 is required.
3. C0704 - If N407 is present, then N404 is required.

Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

Loop Item Identification

Pos: 0100	Repeat: 10000
Mandatory	
Loop: LIN	Elements: N/A

User Option (Usage): Must use

Purpose: To specify basic item identification data

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0100	LIN	Item Identification	M	1		Must use
0300	PID	Product/Item Description	M	10		Must use
3200		Loop QTY	M		99	Must use

LIN Item Identification

Pos: 0100	Max: 1
Detail - Mandatory	
Loop: LIN	Elements: 7

User Option (Usage): Must use

Purpose: To specify basic item identification data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
LIN01	350	Assigned Identification	O	AN	1/20	Used
		Description: Alphanumeric characters assigned for differentiation within a transaction set				
LIN02	235	Product/Service ID Qualifier	M	ID	2/2	Must use
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		CodeList Summary (Total Codes: 519, Included: 1)				
		<u>Code</u> <u>Name</u>				
		VN Vendor's (Seller's) Item Number				
LIN03	234	Product/Service ID	M	AN	1/48	Must use
		Description: Identifying number for a product or service				
LIN04	235	Product/Service ID Qualifier	X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		CodeList Summary (Total Codes: 519, Included: 2)				
		<u>Code</u> <u>Name</u>				
		SK Stock Keeping Unit (SKU)				
		User Note 1:				
		Frontgate and Grandin Road assigned SKU Number				
		UP UCC - 12				
LIN05	234	Product/Service ID	X	AN	1/48	Used
		Description: Identifying number for a product or service				
LIN06	235	Product/Service ID Qualifier	X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		CodeList Summary (Total Codes: 519, Included: 2)				
		<u>Code</u> <u>Name</u>				
		SK Stock Keeping Unit (SKU)				
		User Note 1:				
		Frontgate and Grandin Road assigned SKU Number				
		UP UCC - 12				
LIN07	234	Product/Service ID	X	AN	1/48	Used
		Description: Identifying number for a product or service				

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
------------	-----------	---------------------	------------	-------------	----------------	--------------

Syntax Rules:

1. P0405 - If either LIN04 or LIN05 is present, then the other is required.
2. P0607 - If either LIN06 or LIN07 is present, then the other is required.
3. P0809 - If either LIN08 or LIN09 is present, then the other is required.
4. P1011 - If either LIN10 or LIN11 is present, then the other is required.
5. P1213 - If either LIN12 or LIN13 is present, then the other is required.
6. P1415 - If either LIN14 or LIN15 is present, then the other is required.
7. P1617 - If either LIN16 or LIN17 is present, then the other is required.
8. P1819 - If either LIN18 or LIN19 is present, then the other is required.
9. P2021 - If either LIN20 or LIN21 is present, then the other is required.
10. P2223 - If either LIN22 or LIN23 is present, then the other is required.
11. P2425 - If either LIN24 or LIN25 is present, then the other is required.
12. P2627 - If either LIN26 or LIN27 is present, then the other is required.
13. P2829 - If either LIN28 or LIN29 is present, then the other is required.
14. P3031 - If either LIN30 or LIN31 is present, then the other is required.

Semantics:

1. LIN01 is the line item identification

Comments:

1. See the Data Dictionary for a complete list of IDs.
2. LIN02 through LIN31 provide for fifteen different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

PID Product/Item Description

Pos: 0300	Max: 10
Detail - Mandatory	
Loop: LIN	Elements: 3

User Option (Usage): Must use

Purpose: To describe a product or process in coded or free-form format

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PID01	349	Item Description Type	M	ID	1/1	Must use
Description: Code indicating the format of a description						
CodeList Summary (Total Codes: 3, Included: 1)						
<u>Code</u> <u>Name</u>						
F Free-form						
PID02	750	Product/Process Characteristic Code	M	ID	2/3	Must use
Description: Code identifying the general class of a product or process characteristic						
CodeList Summary (Total Codes: 238, Included: 1)						
<u>Code</u> <u>Name</u>						
08 Product						
PID05	352	Description	M	AN	1/80	Must use
Description: A free-form description to clarify the related data elements and their content						

Syntax Rules:

1. C0403 - If PID04 is present, then PID03 is required.
2. R0405 - At least one of PID04 or PID05 is required.
3. C0703 - If PID07 is present, then PID03 is required.
4. C0804 - If PID08 is present, then PID04 is required.
5. C0905 - If PID09 is present, then PID05 is required.

Semantics:

1. Use PID03 to indicate the organization that publishes the code list being referred to.
2. PID04 should be used for industry-specific product description codes.
3. PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
4. PID09 is used to identify the language being used in PID05.

Comments:

1. If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
2. Use PID06 when necessary to refer to the product surface or layer being described in the segment.
3. PID07 specifies the individual code list of the agency specified in PID03.

Loop Quantity Information

Pos: 3200	Repeat: 99
Mandatory	
Loop: QTY	Elements: N/A

User Option (Usage): Must use

Purpose: To specify quantity information

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
3200	QTY	Quantity Information	M	1		Must use
3550	DTM	Date/Time Reference	M	1		Must use

QTY Quantity Information

Pos: 3200	Max: 1
Detail - Mandatory	
Loop: QTY	Elements: 3

User Option (Usage): Must use

Purpose: To specify quantity information

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
QTY01	673	Quantity Qualifier	M	ID	2/2	Must use

Description: Code specifying the type of quantity

CodeList Summary (Total Codes: 1123, Included: 2)

Code Name

33 Quantity Available for Sale (stock quantity)

User Note 1:

Mandatory

63 On Order Quantity

QTY02	380	Quantity	M	R	1/15	Must use
-------	-----	----------	---	---	------	----------

Description: Numeric value of quantity

QTY03	C001	Composite Unit of Measure	M	Comp		Must use
-------	------	---------------------------	---	------	--	----------

Description: To identify a composite unit of measure (See Figures Appendix for examples of use)

QTY03-01	355	Unit or Basis for Measurement Code	M	ID	2/2	Must use
----------	-----	------------------------------------	---	----	-----	----------

Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken

CodeList Summary (Total Codes: 844, Included: 1)

Code Name

EA Each

Syntax Rules:

1. R0204 - At least one of QTY02 or QTY04 is required.
2. E0204 - Only one of QTY02 or QTY04 may be present.

Semantics:

1. QTY04 is used when the quantity is non-numeric.

User Note 1:

Every item should be included with the quantity available today, even if the quantity is zero. If additional quantities are on order, the QTY loop should be repeated with the future date using QTY01 = 63.

DTM Date/Time Reference

Pos: 3550	Max: 1
Detail - Mandatory	
Loop: QTY	Elements: 2

User Option (Usage): Must use

Purpose: To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use

Description: Code specifying type of date or time, or both date and time

CodeList Summary (Total Codes: 1280, Included: 1)

Code Name

018 Available

DTM02	373	Date	M	DT	8/8	Must use
-------	-----	------	---	----	-----	----------

Description: Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year

Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

CTT Transaction Totals

Pos: 0100	Max: 1
Summary - Optional	
Loop: N/A	Elements: 1

User Option (Usage): Used

Purpose: To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	N0	1/6	Must use

Description: Total number of line items in the transaction set

Syntax Rules:

1. P0304 - If either CTT03 or CTT04 is present, then the other is required.
2. P0506 - If either CTT05 or CTT06 is present, then the other is required.

Comments:

1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

SE Transaction Set Trailer

Pos: 0200	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments	M	N0	1/10	Must use
Description: Total number of segments included in a transaction set including ST and SE segments						
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set						

Comments:

1. SE is the last segment of each transaction set.